## **Detailed Specifications**

## **ADMET eXpert 2600 Dual Column Testing System**



Model		2601 Table Top	2608 Table Top	2610 Table Top	2611 Table Top	2612 Table Top	2613 Table Top	2653 Floor	2654 Floor	2655 Floor	2656 Floor	2657 Floor
Load Capacity	lbf	50	450	1,125	2,250	5,620	11,250	11,250	22,500	33,750	45,000	67,500
	kN	0.22	2	5	10	25	50	50	100	150	200	300
	kgf	22.68	200	500	1,000	2,500	5,100	5,100	10,200	15,300	20,400	30,600
Maximum	in/min	2	100	40	40	20	20	20	20	20	20	20
Speed	mm/min	50	2,540	1,016	1,016	508	508	508	508	508	508	508
Minimum	in/min	0.00002	0.0002	0.0001	0.0001	0.000002	0.000002	0.000002	0.000002	0.000002	0.000002	0.000002
Speed	mm/min	0.0005	0.005	0.0025	0.0025	0.00005	0.00005	0.00005	0.00005	0.00005	0.00005	0.00005
Maximum Force at Full Speed	lbf kN	50 0.22	450 2	1,125 5	2,250 10	5,625 25	11,250 50	11,250 50	22,250 100	33,750 150	45,000 200	67,500 300
Total Cross- head Travel'	in mm	29 735	48 1,219	48 1,219	48 1,219	46 1,168	46 1,168	43 1,092	42 1,067	42 1,067	44 1,117	51 1,300
Total Vertical	in	42.5	54	54	54	52	52	49	48	48	52	60
Test Space <sup>1</sup>	mm	1,078	1,371	1,371	1,371	1,320	1,320	1,245	1,219	1,219	1,321	1,524
Space Between	in	12	16.8	16.8	16.8	16.8	16.8	22	22	22	22	22
Columns	mm	300	426	426	426	426	426	558	558	558	558	558
Height	in	44	71	71	71	71	71	85	85	85	93	102
	mm	1,120	1,803	1,803	1,803	1,803	1,803	2,159	2,159	2,159	2,362	2,591
Width	in	23	34	34	34	34	34	41	41	41	43	46
(Frame Only)	mm	600	864	864	864	864	864	1,041	1,041	1,041	1,092	1,168
Depth	in	17.7	20.5	20.5	20.5	20.5	20.5	23	23	23	26	26
	mm	450	520	520	520	520	520	584	584	584	660	660
Weight	lbf	100	330	330	330	600	600	1,600	1,800	2,000	2,200	2,400
	kgf	45	150	150	150	275	275	730	820	910	1,000	1,100